



ADJUSTABLE PLASTIC PEDESTAL TECHNICAL DATA SHEET

ACCESSORIES

AUTOLEVELLING



TBR-TS3
AUTOLEVELLING HEAD
CROSS 3 mm



TBR-C
AUTOLEVELLING
HEAD.



TBR-WH
AUTOLEVELLING HEAD FOR
WOODEN BEAM HEAD
HOLDER - 40-50 mm



TBR-WHS
AUTOLEVELLING
HEAD FOR WOODEN
BEAM HEAD SIMPLE -
up to 80 mm.

GENERAL ACCESSORIES



TBF-SM3
Straight spacer 3mm.
(bag 40 units) Height
16mm.



TBF-SC3
Plus shape formed joint
strips can be sit in the
middle of pedestal and
have 3mm thickness.
Height 16mm.



TBF-W
This type of carcass
assembly equipment
is put every point on
pedestal except central
point.



TBF-WH
X formed Carcass
Assembly Equipment
does sit on top and
central of the pedestal.



TB-A
DAMPER TB-A
(40 Units Bags)



TB-CL
ADJUSTABLE HEIGHT
COMPLEMENT.



TBR-CR
FIX COLLAR
TB-CR.



TB-DN
Slope Correctors, sit
under bottom pedestal,
avoids all impacts from
drain slopes.

OTHER ACCESSORIES



TB-SP
WALL SPACER



TB-MBF
METALLIC
BOTTOM
FRAME.



TB-MTF
METALLIC TOP
FRAME.



TBR-AK
HEIGHT
ADJUSTABLE KEY



TB-PV
SCREW WIND
PROTECTOR TB-
PV (100 units
Bag).

Application

Adjustable pedestals TAYG allow to regulate accurate and permanent height. Can support any type of ceramic or timber decking, stone, concrete paving or flag material, as well as fiber glass or metal grid panels.

Suitable for any kind of stable substrate, including applications directly over insulation panels.

Covering size	m ² / pcs.
30 x 30 cm	13,80
40 x 40 cm	7,80
30 x 60 cm	6,70
40 x 60 cm	5,20
50 x 50 cm	5,00
60 x 60 cm	3,50

INDUSTRIAS TAYG, S.L.U
Avenida Real de Madrid (Norte), 70

46469 BENIPARRELL

VALENCIA – SPAIN

www.tayg.com